

DISTRIBUTEURS A COMMANDE PNEUMATIQUE

Sommaire



normes	orifices/positions	fonction	type de raccordement										pression maxi (bar)	débit à 6 bar l/min (ANR)	type	illustration	série	page
			NF		NO		ØG		1		1 1/4							
VDMA/ISO15407-1 ISO 5599-1			6	1/8	1/4	3/8	1/2	3/4	1	1 1/4	1 1/2							
Distributeurs à clapets																		
		● ●				■ ■						⊥	12	700-1750	DM		261 262	P415
	3/2	● ●					■ ■	■ ■	■ ■	■ ■	■ ■		12/16	4500-35000	DH		284 285 286	P420
		●						■ ■			■ ■	⊥	16	3000-31500	DP		266 267 268	P425
ISO		●				■ ■	■ ■	■ ■	■ ■				⊥	10	5675	ISO 3		G34
	4/2						■ ■				■ ■	⊥	16	2940-31500	DP		266 267 268	P440
				■ ■	■ ■								10	210-840			263 264	P433
						■ ■	■ ■						⊥	12	700-1750	DM		261 262

DISTRIBUTEURS A COMMANDE PNEUMATIQUE

normes	orifices/positions	fonction	type de raccordement									à appliquer	pression maxi (bar)	débit à 6 bar l/min (ANR)	type	illustration	série	page	
			NF NO 6 1/8 1/4 3/8 1/2 3/4 1 1 1/4 1 1/2 à plan de pose Namur à coupleurs Ø extf. (mm) tarudé ØG à applique																
VDMA/ISO15407-1 ISO 5599-1	3/2	●											10	860 3000 3800			551 552 553	P410-1 P460-1	
	3/2	●											8	400 175-1050 600-1050			519 520 521	P450	
	5/2											10	1000-1700			L1 L2	P455-1		
	5/3																		
	5/2												8	500	ISO 02		538 CL18	P468-1 P468-3	
	5/3																		
	VDMA - ISO	2x3/2 5/2 5/3											10	1150	ISO 01		539 CL26	P466-1 P466-3	
ISO	5/2 5/3											10/12	1400 2800 4200	ISO 1 ISO 2 ISO 3		541 542 543	P470-1		
ISO	5/2 5/3											12	6300-7000	ISO 4		544	P471-1		
ISO	5/2 5/3											10	1400 2800 4200	ISO 1 ISO 2 ISO 3		E12 E23 E34	P472-1		